Hankook Motorsports 10808 FM 1625 Austin, TX 78747 800-287-5013 info@hankookmotorsports.com



Hankook Tire Specifications

2019 F4 U.S CHAMPIONSHIP & F3 AMERICAS

Hankook has been a proud partner of Formula 3 and Formula 4 aross the globe for many years, and you may already know us from FIA F3 or British F4. We are very excited to add F4 United States and F3 Americas as our partners for the coming years. We believe in devoting resources to developing young drivers and hope that this platform will provide the skills you need to be well on your way to F1 superstardom!

Enclosed you will find information regarding the Hankook brand, tire technical data, tire pricing, ordering, and trackside fitting process. Should you have any technical questions, please contact Danny van Dongen at 305-809-0356 or email him at danny@hankookmotorsports.com.



Statement of Confidentiality

This proposal and supporting materials contain confidential and proprietary business information of Hankook Motorsports. These materials may be printed or photocopied for use in evaluating the proposed project, but are not to be shared with other parties.



Hankook Tire is committed to the future of motorsports

Hankook Tire encourages all drivers around the world to pursue their passion by sponsoring competitions and racing teams. In motorsports, where limits are pushed and overcome and true potential is realized, our technological know-how is fully demonstrated.

By sponsoring a wide range of motorsports competitions and teams at home and abroad, Hankook Tire is inspiring drivers worldwide to overcome the challenges posed by speed and to take on new possibilities. Through Hankook Tire's innovative technology, drivers around the world can enjoy achieving new goals and setting new records. Hankook Tire is raising the bar of motorsports for a passionate driving culture for those who are thrilled about the world of motorsports competition.

Take a look at some of our current sponsored race series to see how Hankook supports motorsports around the globe.







Vision for 2020

Hankook Tire has grown to be the fifth largest in tire production capacity and seventh in sales internationally. We have 7 production sites, 30 sales branches and 5 R&D centers around the world. This is a result of Hankook Tire's spirit of challenge, commitment, and hard work. Without breaking stride, our vision is to lead the world's driving industry, and become a major global player by providing our customers value and pleasure.

What we do

We strive to be the best at what we do

- ▶ Production Capacity: 104 million units in 2017
- Local offices in 30 countries, 5 R&D centers located in Korea, USA, Germany, China and Japan
- ▶ 8 production facilities in Korea (2), China (3), USA, Hungary and Indonesia



Hankook in F3 and F4



Formula 3The FIA Formula 3 European Championship is a gateway to becoming an international F1 driver and talented young race car drivers from all over the world are realizing their dream to be among the world's best with Hankook Tire.

Hankook Tire has actively sponsored talented up-and-coming drivers as an official corporate sponsor of FIA Formula 3 since 2012 and the British and Australian F4 series since 2015.



Specially designed single-seater slicks and wets

▶ Ventus F200 (Dry)

▶ Ventus Z207 (Wet)

▶ Circuit / Slick

Top-notch performance tire with high mileage and consistency on a dry surface. Radial Construction. Directional tires.

As a dry tire, the F200 is a high-tech slick tire which has excellent grip ability and continuous performance even in the limit of high speed driving.

▶ Circuit / Wet

Extremely reliable circuit tire to be used exclusively on wet surfaces

As a wet tire, the Z207 prevents hydroplaning whilst maintaining excellent controlling stability and the best drainage performance.



F3 Tire Data and Spring Rates (dry only)

Hankook F3ES Tire technical data			
F200 - SLICK TIRE			
Tire Size		230/560R13 F200	280/580R13 F200
Permitted Rim		9.5"~10.5"	11.5"~12.5"
Optimum Rim (Measuring)		8.5"	10.5"
Tread Width (mm)		230	280
Section Width (mm)		282	335
Overall Diameter (mm)		551	572
Overall Circumference (mm)		1731	1797
Revolutions/km		599.3	577.3
Recommended Inflation	Cold	1.1~1.2	1.1~1.2
Pressure (bar)	Hot	1.5~1.6	1.5~1.6
Recommended Camber		-2.5~3.5	-2.0~2.5
Recommended Toe		20' OUT	10' IN

America Tire Tech	nical Data (Dry Tire)		
			25-10-2018
	Size	230/560R13	280/580R13
Treat	d Pattern	F200	F200
Spec	ification	C72	C72
Sidewall	Decal Color		
Rim S	lize (Inch)	10.0JX13	12.0JX13
Inflation P	ressure (kgf/cm)	1.5	1.5
Vertical load (kgf)	Spring rates (kgf/mm)		
100	Vertical	20.6	22.8
	Lateral	13.9	14.4
	Torsional	17.3	20.6
	Vertical	20.0	22.7
200	Lateral	16.0	16.3
	Torsional	26.0	25.7
	Vertical	19.7	21.8
300	Lateral	16.2	16.6
	Torsional	27.6	26.5



F4 Tire Data and Spring Rates

F4 Tire Technical Data (Dry Tire)

F4 Tire Technical Data (Wet Tire)

Static Spring Rates

S	lize	180/550R13	240/570R13
Tread	Pattern	F200	F200
Specification		F4(C92)	F4(C92)
Sidewall I	Decal Color		
Rim Si	ze (Inch)	8.5JX13	10.5JX13
Inflation Pressure (kgf/cm²)		1.5	1.5
Vertical load (kgf)	Spring rates (kgf/mm)		
150	Vertical	19.2	21.3
	Lateral	13.7	13.2
	Torsional	323.0	282.4
180	Vertical	19.6	20.4
	Lateral		
210	Vertical	19.6	20.8
	Lateral		
240	Vertical	20.0	21.3
	Lateral		

Static Spring Rates

S	ize	180/550R13	240/570R13
Tread	Pattern	Z206	Z207
Speci	fication	F4	F4
Sidewall	Decal Color		
Rim Si	ze (Inch)	8.5JX13	10.5JX13
Inflation Pro	essure (kgf/cm²)	1.5	1.5
Vertical load (kgf)	Spring rates (kgf/mm)		
	Vertical	16.7	18.2
150	Lateral	10.7	11.1
	Torsional	205.5	259.8
100	Vertical	17.0	18.9
180	Lateral		-
210	Vertical	17.9	18.5
	Lateral		_
240	Vertical		
	Lateral		

F4 Tire Technical Data (Dry Tire)

Dimension

Size	180/550R13	240/570R13
Tread Pattern	F200	F200
Specification	F4(C92)	F4(C92)
Sidewall Decal Color		
Rim Size (Inch)	8.5JX13	10.5JX13
Recommanded (Rim Width)	8.0 - 9.0	10.0 - 11.0
Inflation Pressure (kgf/cm²)	1.5	1.5
Overall Diameter	551mm	574mm
Section Width	241mm	290mm
Tread Width	200mm	250mm

F4 Tire Technical Data (Wet Tire)

Dimension

Size	180/550R13	240/570R13
Tread Pattern	Z206	Z207
Specification	F4	F4
Sidewall Decal Color	-	
Rim Size (Inch)	8.5JX13	10.5JX13
Recommanded (Rim Width)	8.0 - 9.0	10.0 - 11.0
Inflation Pressure (kgf/ont)	1.5	1.5
Overall Diameter	552mm	575mm
Section Width	239mm	295mm
Tread Width	200mm	250mm



Pricing and Ordering

Category	Tire Size	Model	Price
F3	230/560R13	Slick/Wet	\$280
F3	280/580R13	Slick/Wet	\$320
F4	180/550R13	Slick/Wet	\$260
F4	240/570R13	Slick/Wet	\$290

Order Details

- 1. All prices are exclusive of tax and shipping.
- 2. If you provide a sales tax resale certificate, no sales tax will be applied.
- 3. Orders can be placed by sending an email with: Team Name, Contact Person, Shipping Address, Phone Number and Billing Address to f3f4@hankookmotorsports.com or by phone at 800-287-5013.
- 4. Orders made for delivery at an event must be made at least 2 weeks prior to the event.
- 5. Delivery to the track at official events is free if orders are placed 2 weeks or more prior to the event. Event orders made less than 2 weeks prior to an event may incur a shipping charge.
- 6. For orders received at an official event, payment is due within 7 calendar days after event.
- 7. For orders shipped directly to you, payment is due prior to shipment.
- 8. We ship via UPS and use both ground and freight services.
- 9. You can make arrangements to pick tires up from our facility in Austin, TX free of charge.
- 10. We accept credit cards, cash, checks, bank transfer (echeck), wire transfer and PayPal.
- 11. We can keep your credit card on file for future invoices.



Services and Trackside Fitting Regulations

Trackside Service and Support - Provided by Race Tires Sales and Service Inc.

Trackside support is our business. We started our motorsports careers as drivers and understand the demanding needs of teams, drivers and engineers. That's why we provide much more than just tire fitting - we provide a total tire service solution. We always have knowledgeable staff on site to answer even the toughest technical questions and provide accurate feedback to the competitors and the teams. Safety is paramount and we go to great lengths to ensure proper tire care and fitting services. We help the teams monitor tire usage and get the most out of their tires; both in longevity and performance.

- ▶ Engineers at every event provide technical answers, setup guides and monitor tires for wear
- ▶ Full fitting services including multiple lines of dismount, mount, balance and recycling
- ▶ Hankook branded tire fitting tent with top quality tire fitting equipment
- ▶ Barcode scanning system for tire usage control
- Multiple payment options for teams onsite include credit card, checks, bank transfer and PayPal

Trackside Tire Service Procedure

- 1. Wheels must be cleaned, weights removed and valve stem taken out.
- 2. Team name and car number must be visible on the wheel.
- 3. You must confirm your fitting request with on site Hankook personnel when you bring wheels for fitting services. Do not drop or leave unattended wheels or tires.
- 4. You must sign a receipt for all tires/services when you pick up tires/wheels.
- 5. You will be charged \$25 for every tire fit on the track.
- 6. We can recycle or dispose of used tires at the track for \$5 per tire.



Tire Photos























